



PROTEOR

USA

Knee and Foot Selection Chart

KNEES



1M
SERIES

1M112
SERIES

1M102
SERIES

Symphony

matik

ALLUX

HYTREK

EASY
RIDE

Item Number for order	1M1	1M10	1M10HD	1M10HD	1M112	1M113	1M102	1M102V	1M102HD	1M102HD	NK6	NK6-L	NK6 SH	NK6 SH-L	IP200	IP200HD	NE-24	NE-24SH	IP131	IP131-KD	IP650	
Product Description	K1m joint friction adjustment, lock with adjustable stop, socket rotation adjustment +/- 15°				Compact 4 axis, joint friction and extension assist adjustments, socket rotation adjustment +/- 15°		Joint friction adjustment, optional lock, extension assist adjustment, socket rotation adjustment +/- 15°				6-bar hydraulic, adjustable stance flexion, user-adjustable manual lock				4 axis pneumatic, flexion and extension adjustments, extension spring		4-bar MPK that controls both stance and swing phase		Single axis, hydraulic regulation of stance and swing phase, manual lock.		High impact, multisport knee	
Product Weight	345g	355g	375 g		320g	240g	565g	575g	500g	525g	920g	970g	960g	1010g	743g		1510g		1285g	1285g	1264g	
TH / BH / H	99 / 58 / 13		102 / 59 / 14		175 / 75 / 5 11		184 / 113 / 12				7.75" (197mm)		7.5" (191mm)		204/175/11.5	195/172/8	11.5" (295mm)	11.33" (287mm)	232/177/33	222/174/33		
Materials	Aluminum, Steel				Aluminum		Aluminum, Steel				Aluminum, Titanium				Aluminum, SS				Aluminum, SS, Titanium		Aluminum Alloy	
Knee Flexion	130°				165°		160°				170°				170°		155°		120°		130°	
Proximal Connector	1K40 - 1K164 - 1K180 -1K163				1K40 - 1K164 - 1K180 -1K163		1K40 - 1K164 - 1K180 -1K163				Pyramid		Threaded Top		Pyramid		Threaded Top		Pyramid	Threaded Top	Pyramid	Threaded Top
Distal connector	30mm tube		34mm tube		22mm tube	30mm tube	30mm tube		34mm tube		Pyramid				Pyramid		Pyramid		34mm tube		Pyramid	
Max Patient Weight	220 lbs 100 kg		275 lbs 125 kg		99 lbs 45 kg	176 lbs 80 kg	220 lbs 100 kg		275 lbs 215 kg		220 lbs 100 kg	275 lbs 125 kg		275 lbs 125 kg	275 lbs 125 kg	275 lbs 125 kg		275lbs / 125kg (K3) 220lbs / 100kg (K4)		330lbs 150 kg	275lbs 125kg	
Activity Level	K1				K1 - K2		K1 - K2				K3				K2 - K3		K3 - K4		K3 - K4		K3 - K4	
Water Resistance	-				-		-				-				-		IP42		Weather Resistant		Water Resistant	

FEET



RUSH
HiPro

RUSH
RAMPAGE

RUSH
RAMPAGE

RUSH
kid

RUSH
Chopart

RUSH
ROGUE

RUSH
ROVER

Product Description	Highly dynamic, high-energy return,smooth roll over, all-terrain and waterproof	Highly dynamic, high-energy return, smooth roll over, cosmesis ready, all-terrain and waterproof	Low-profile, highly dynamic, high-energy return, smooth roll over, cosmesis ready, all terrain and waterproof	Pediatric foot, low-profile, highly dynamic, high-energy return, smooth roll over, all-terrain and waterproof	Chopart, highly dynamic, high-energy return, smooth roll over, all-terrain and waterproof	Vertical loading pylon, highly dynamic, high-energy return, smooth roll over, all-terrain and waterproof	Build height of just over two inches, smooth roll through, dynamic toe-off
Product Weight	920g	850g	805g	505g	380g	1155g	950g
Max Patient Weight	365 lbs	365 lbs	365 lbs	125 lbs	365 lbs	365 lbs	365 lbs
Materials	Glass Composite	Glass Composite	Glass Composite	Glass Composite	Glass Composite	Glass Composite	Glass Composite
Build Height	22-24 cm = 6.5" / 165 mm	22-24cm = 6.825" / 168mm	22-24cm = 4.5" / 114mm		22-24cm = 1" / 25mm	22-24cm = 6.5" / 165mm	22-24cm = 2.125" / 54mm
	25-27 cm = 6.8" / 175 mm	25-27cm = 7.125" / 181mm	25-27cm = 4.75" / 121mm	19-21cm = 2" / 51mm	25-27cm = 1.125" / 29mm	25-27cm = 7" / 178mm	25-27cm = 2.375" / 60mm
	28-29 cm = 7.125" / 181 mm	28-29cm = 7.25" / 184mm	28-29cm = 4.75" / 121mm		28-29cm = .875" / 22mm	28-29cm = 7.125" / 181mm	28-30cm = 2.5" / 64mm
Heel Rise	3/8" / 10 mm	3/8" / 10 mm	3/8" / 10 mm	3/8" / 10 mm	3/8" / 10 mm	3/8" / 10 mm	3/8" / 10 mm
Foot Shell	Light or Dark	Light or Dark	Light or Dark	Light or Dark	Light or Dark	Light or Dark	Light or Dark
Activity Level	K3 - K4	K3 - K4	K3 - K4	K3 - K4	K3 - K4	K3 - K4	K3 - K4
Water Resistance	Waterproof (fresh or salt water)	Waterproof (fresh or salt water)	Waterproof (fresh or salt water)	Waterproof (fresh or salt water)	Waterproof (fresh or salt water)	Waterproof (fresh or salt water)	Waterproof (fresh or salt water)

HiPro, RAMPAGE, ROGUE, ROVER module selection according to activity and weight										
Weight	lbs	0-105	106-140	141-175	176-210	211-245	246-280	281-315	316-350	351-365
kg	0-48	49-64	65-79	80-95	96-111	112-127	128-143	144-159	160-166	
Activity level										
Low	1	2	3	4	5	6	7	8	9	
Moderate	1	2	3	4	5	6	7	8	9	
High	1	2	3	4	5	6	7	8	9	
High impact	2	3	4	5	6	7	8	9	-	

RAMPAGE LP module selection according to activity and weight									
0-105 lbs	106-140	141-175	176-210	211-245	246-280	281-315	316-350	351-365	
0-48	49-64	65-79	80-95	96-111	112-127	128-143	144-159	160-166	
1	2	3	4	5	6	7	8	9	
1	2	3	4	5	6	7	8	9	
2	3	4	5	6	7	8	9	-	
3	4	5	6	7	8	9	-	-	

Kid module selection according to activity and weight												
0-30	31-45	46-60	61-75	76-90	91-105	106-120	131-135					
0-14	15-20	21-27	28-34	35-41	42-48	49-54	55-61					
1P	2P	3P	4P	5P	6P	7P	8P					
1P	2P	3P	4P	5P	6P	7P	8P					
1P	2P	3P	4P	5P	6P	7P	8P					
2P	3P	4P	5P	6P	7P	8P						

Chopart module selection according to activity and weight																
0-70	71-105	106-140	141-175	176-210	211-245	246-280	281-315	316-350	351-365							
0-32	33-48	49-64	65-79	80-95	96-111	112-127	128-143	144-159	166-166							
0	1	2	3	4	5	6	7	8	9							
0	1	2	3	4	5	6	7	8	9							
0	1	2	3	4	5	6	7	8	9							
1	2	3	4	5	6	7	8	9	-							

*Product weight based on size 26cm, Cat 4 foot module with spectra sock and foot shell; RUSH Kid weight based on 20cm Cat 4. **Build height based on size 23cm, 26cm, or 29cm Cat 4 foot module with spectra sock, foot shell and 10mm heel rise.

NOTE: Increasing category numbers indicate increased keel response. FOR BILATERAL PATIENTS: Increase by one category for added stability.

FEET



GERY

dynaStep

dynaStar

dynaTREK

EASY
RUN

RUSH
Foot
COLLECTION

RUSH
H2O
COLLECTION

Product Description	Comfortable, low-level K2 foot, accommodates heel heights from 1.2 to 1.8" 100% waterproof	K2 foot, suitable for transtibial and transfemoral amputees, available with multiaxis ankle joint (shown above)	High stability, excellent comfort due to link between the keel and heel strut, available in 4 sizes	All-terrain foot, optimal inversion/eversion & energy return, great for transtibial and transfemoral patients	Curved fiberglass blade, rotatable pyramid adapter, anti-slip sole, available in 6 stiffness categories and 6 vibrant designs.	Elevated vacuum system, available for RAMPAGE, RAMPAGE LP, ROGUE and HiPro, minimal maintenance required	Integrated Vibram® sole and custom molded toe wrap, ideal for shower and watersports, available for RAMPAGE, RAMPAGE LP, ROGUE, and HiPro
Max Patient Weight	330lbs / 150 kg	176lbs / 80kg - 220lbs / 100kg	99lbs / 45kg - 275 lbs / 125kg	330 lbs / 150 kg	88lbs / 40kg - 242lbs / 110kg	365 lbs	365 lbs
Activity Level	K1 - K2	K2	K2 - K3	K3 - K4	K3 - K4	K3 - K4	K3 - K4

	RAMPAGE	HiPro	RAMPAGE LP	ROGUE	RAMPAGE	HiPro	RAMPAGE LP	ROGUE
Product Weight	860g	830g	815g	1165g	695g	765g	650g	1000g
Build height 22-24 cm	6.625" / 168mm	6.5" / 165mm	4.5" / 114mm	6.5" / 165mm	6.25" / 159mm	6" / 152mm	4.125" / 105mm	6" / 152mm
Build height 25-27 cm	7.125" / 181mm	6.875" / 175mm	4.75" / 121mm	7" / 178mm	7.125" / 181mm	6.25" / 159mm	4.125" / 105mm	6.25" / 159mm
Build height 28-29 cm	7.25" / 184mm	7.125" / 181mm	4.75" / 121mm	7.125" / 181mm	7" / 178mm	6.875" / 175mm	4.375" / 111mm	6.875" / 175mm
Heel Rise		3/8" / 10mm						



PROTEOR

USA

1236 West Southern Avenue #101, Tempe, AZ 85282 • 855.450.7300

shop.proteorusa.com



#HUMANFIRST